

Flush mount access doors specifications

INSULATED

FMI85GA
FMI126GA
FMI1810GA
FMI2114GA
FMI2517GA

UNINSULATED

FMU85GA
FMU126GA
FMU1810GA
FMU2114GA
FMU2517GA

STANDARD CONSTRUCTION

- ✓ Galvanized Steel
- ✓ Positive cam lock fastenings.
- ✓ One piece extruded gasket for positive seal.
- ✓ The door is two die-formed and seamless panels in a sandwich construction.
- ✓ Thermal, Acoustic and Fire Retardant insulation.
- ✓ Pre-punched holes in both flanges of frame.
- ✓ The frame is die-formed and seamless.

FEATURES

- ✓ Oval Shape for ease of installation.
- ✓ Cut-out template provided.
- ✓ Suitable for insulated or uninsulated duct.
- ✓ Safety Chain (Optional)

Model	FMI/U85GA		FMI/U126GA		FMI/U1810GA		FMI/U2114GA		FMI/U2517GA	
	Nom. Size	200X125	8X5	300X150	12X6	460X250	18X10	550X350	22X14	650X450
	mm	in	mm	in	mm	in	mm	in	mm	in
A	200	7 7/8	300	11 7/8	460	18 1/4	550	21 5/8	650	25 5/8
B	125	5	150	6	260	10 1/4	350	13 3/4	450	17 3/4
C	240	9 1/2	350	13 1/4	500	19 5/8	590	23 1/4	690	27 1/8
D	165	6 1/2	200	7 7/8	300	11 7/8	400	15 3/4	500	19 5/8

